



FM430
Barracuda
fixed mount
barcode scanner



FEATURES

Megapixel camera.

The FM430 Barracuda is a barcode scanning powerhouse. No matter what type of barcode is presented, the megapixel camera allows users to scan 1D and 2D barcodes, including very small ones, with impressive speed and ease.

Snappy, also in less than perfect conditions.

A combination of the IR sensor and the light sensor helps to keep workers moving, even in low light conditions. Its strong, white light ensures barcodes are always well lit.

Handsfree or manual scanning.

Companies looking for automatic scanning to relieve manual labor can set up the FM430 Barracuda for handsfree scanning. Alternatively, a manual trigger button can be used if preferred.

Intelligent programming.

The sensors of the FM430 Barracuda automatically adjust the brightness of supplementary lighting based on the light that reflects off the barcode. This also makes it an optimal solution for scanning from mobile phone screens. Depending on the application, the scanner can be set to optimally read from close and long distance.

Reliable outdoor use.

With an IP rating of 54, this fixed mount scanner can be placed in a housing and used outdoors without worrying about dust or moisture.

Bright laser aimer (optional).

The FM430 Barracuda is available with a red cross laser that makes scanning easy and intuitive, even for the most inexperienced users.

Application Scenarios

Self-service kiosks used in e-commerce • express delivery services, access control • loyalty • mobile payment • events ticket redemption • gaming cash outs • postal services • transport boarding passes • parking ticket machines • production line.

FM430 Barracuda

fixed mount barcode scanner

newland-id.com

Performance	Image Sensor	1280 * 800 CMOS		
	Illumination	White LED		
	Aiming	Red Cross Laser Aimer or green LED		
	Symbologies	2D	PDF417, QR Code, Data Matrix, Aztec, CSC, Maxicode, Micro QR, Micro PDF417, GM, Code One.	
		1D	EAN-13, EAN-8, UPC-A, UPC-E, Code 128, Code 39, Codabar, UCC/EAN 128, RSS, ITF, ITF-14, ITF6, Standard 25, Matrix 25, COOP 25, Industrial 25, Plessey, MSI Plessey, Code 11, Code 93, Code 49, Code16K.	
	Resolution*	≥3mil		
	Typical Depth of Field*	EAN-13	55-360mm (13mil)	
		Code 39	70-180mm (5mil)	
		PDF 417	55-160 (6.67mil)	
		Data Matrix	50-170 (10mil)	
		QR Code	40-210mm (15mil)	
	Scan Mode	Sense mode, Continuous mode, Level mode, Pulse mode		
	Scan Angle**	Roll: 360°, Pitch: ±55°, Skew:±55°		
	Field of View	Horizontal 51°, Vertical 32°		
Symbol Contrast	≥25%			
Mechanical/ Electric	Interface	RS-232, USB		
	Dimensions	41.5(W)×49.5(D)×24.3(H)mm		
	Weight	75g		
	Notification	Beep, LED indicator		
	Rated Power Consumption	1622mW (typical)		
	Operating Voltage	5VDC±5%		
	Current @ 5VDC	Operating	276.8mA (typical), 322.7mA (max.)	
		Standby	83.3mA	
Environmental	Operating Temperature	-20°C to 60°C (-4°F to 140°F)		
	Storage Temperature	-40°C to 70°C (-40°F to 158°F)		
	Humidity	5% to 95% (non-condensing)		
	ESD	±14 kV (air discharge), ±8 kV (direct discharge)		
	Drop	1.5m		
	Sealing	IP54		
Certifications	FCC Part15 Class, CE EMC Class B, RoHS, IEC60825, IEC62471, KC			
Accessories	Cable	USB	Used to connect the FM430 to a host device.	
		RS232	Used to connect the FM430 to a host device.	
	Power Adapter	DC5V adapter to power the FM430 with RS232 cable.		

*Testconditions: T=23°C; Illumination=300lux using incandescent lamp; sample barcodes made by Newland.

Version: V1.0

**Testconditions: Scan Distance=(min. DOF + max. DOF)/2; T=23°C; Illumination=300lux using incandescent lamp; 2D: QR Code;10 Bytes; Resolution=15mil; PCS=0.8.

Specifications are subject to change without notice.

Newland EMEA HQ
8 (800) 100 46 22
info@newland-id.com
newland-id.com

D-A-C-H
+49 (0) 6182 82916-16
info@newland-id.de

United Kingdom
+44 (0) 7771 631387
info@newland-id.co.uk

France
+39 (0) 345 8804096
france@newland-id.com

Russia
+31 (0) 345 87 00 33
russia@newland-id.com

Benelux
8 (800) 100 46 22
benelux@newland-id.com

Turkey
+90 (0) 544 538 40 49
turkey@newland-id.com

Ibérica
+34 (0) 93 303 74 66
info@newland-id.es

Middle East
+39 (0) 345 8804096
middleeast@newland-id.com

Italy
+39 (0) 342 0562227
italy@newland-id.com

South Africa
Gauteng: +27 (0) 11 553 8010
Cape Town: +27 (0) 21 9140819
info@newland-id.co.za

Nordic & Baltic
+46 (0) 70 88 47 767
nordic@newland-id.com

Iran
+90 (0) 544 538 40 49
iran@newland-id.com