

EPM 207-HRS

Compact bucket printer with integrated high speed controller



58 mm



Options

- Windows Drivers
- Label / black mark detection sensor
- 300 dpi
- Linux
- Available in white

Applications

- Hand held terminals
- Measuring instruments and analysers
- Medical equipment
- Portable printers and terminals
- Automotive
- Data terminal devices
- EFT POS
- ID Automation

Features

- Fully hot plug printer
- Single power supply from 5 V to 8.5V
- 2 Communication ports: RS232 and USB 2.0
- Programmable consumption
- Full control over printing quality/speed
- Integrated keyboard with paper feed and ON-OFF line push button & LED
- Powerful text & graphic printing modes
- Sleep mode
- Printer setup parameters can be saved in flash
- Easy firmware upgrades
- Patented Door Opening System

Specifications

EPM207-HRS

Print method	Thermal
Number of dots	384
Resolution (dots/mm)	8
Printing width (mm)	48
Paper width (mm)	58
Max. paper thickness (µm)	80
Paper loading	Easy loading
Printing speed (mm/s)	95
Paper detection	Opto sensor
Temperature detection	Thermistor
Head/ Cover-up detection	Combined with opto sensor
Voltage range	5V to 8.5V
Weight (g)	90
Life/reliability	100 km/100M pulses
Operating temperature (°C)	-5 to 50 non cond.
Operating humidity (%)	20 to 85 non cond.
Dimensions (WxDxH mm)	81.6x106.x69
Max. paper roll diameter (mm)	60
Character set	3 resident + downloadable
Character size	8x16, 7x16, 12x20
Character per line (max)	48, 24, 12/54, 27, 13/32, 16, 8
Interfaces	RS232, USB
Graphics	Variable width and offset/double width and height
Barcodes	10 barcodes: normal and rotated 90°
Drivers	Windows, Linux
Black mark detection	Y
Zero power mode (slep mode)	Y
Auto wake-up	Y
Functional keyboard	Y